KWRU WWTP PM Schedule

Equipment: Sludge gear, motor, drive chain (EAST)

Sludge gear, motor, drive chain (WEST)

Grease motor and gearbox QUARTERLY

Grease chain TWICE a YEAR

Change gear box oil ONCE a YEAR (80-90wt oil)

Main Blowers (LAMSON)

Blower #1, #2, #3

Grease blowers and motors QUARTERLY (high speed high temperature grease)

Check filter elements MONTHLY change AS NEEDED

Surge blowers (2) (EAST)

Grease blowers and motors QUARTERLY

Check filter elements MONTHLY change AS NEEDED

Change oil YEARLY (SAE30wt Non detergent)

Surge blower/thickener (WEST)

Grease blower and motor QUARTERLY

Check filter elements MONTHLY change AS NEEDED

Change oil YEARLY (SAE 30wt Non detergent)

Effluent pumps and motors

Grease motors and pumps QUARTERLY

Valves

- 5@ effluent box (1 in ground to wells)
- 3@ wells (in ground)
- 2@ WWTP influent (in ground)
- 4@ filter inlets 2 knife north filters & 2 ball south filter
- 1@ south CCC bypass (in ground)
- 2@ north CCC bypasses (knife valves)
- 4@ mud well

Exercise all valves QUARTERLY